

TOWNSHIP 26 RANGE 01 POINT IDENTIFIER # 400540

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 9 & 10

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

<p>GLO survey by Fred Mensch, Deputy Surveyor - contract #797 dated April 19, 1910 - (DCSO records Vol. 10 Page(s) 4133)</p> <p>-----</p> <p>Set a basalt stone 15x8x6", 10" in the ground for ¼ sec. cor. mkd. ¼ on W face, from which</p> <p> A hemlock, 10" dia., bears S.45°E., 26 lks., mkd: ¼ S10 BT</p> <p> A maple, 8" dia., bears S.3°W., 24 lks., mkd: ¼ S9 BT.</p>
<p>Douglas Co. Surveyors Office - Vernon "Ray" Tracy - March 1970 - C.S. File 52/77-23</p> <p>-----</p> <p>Reported as not found.</p> <p>At point calc. by C. Collins there is an old down maple - however, not accounting for natural erosion of river, this tree would still be too far from river to fit call distance.</p>
<p>Maurice "Ed" Farr - For: Umpqua National Forest - Jan. 1977 - M63-20 - C.S. 58/138</p> <p>-----</p> <p>Set - 1"x36" IP with a 2½" brass cap stamped T26S R1W ¼ S9 S10 PE 5188 1977. From which</p> <p> 22" Hemlock S.84°W., 48.4 ft blazed & scribed "¼ S9 BT"</p> <p> 19" Hemlock S.46°15'E., 24.4 ft. blazed & scribed "¼ S10 BT"</p>
<p>James M. Stanley, ODOT - Sept/Nov. 2007 - St. Hwy 138-011L</p> <p>-----</p> <p>Fd. 2½" BC stamped "PE5188 T26S R1W S9 S10 1977" (10-1-07)</p> <p>N. 611443.088</p> <p>E. 4306028.951</p>
<p> </p>