

TOWNSHIP 26 RANGE 01 POINT IDENTIFIER # 400700

PRIMARY CORNER DESCRIPTION C.C. for Secs. 3 & 4 only, (North)

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by Fred Mensch, Deputy Surveyor, under Contract #797, dated April 19, 1910 - (DCSO records Vol. 10 Page(s) 4135-36)

At a point 22.65 chs. E. of the cor. of secs. 32 and 33, T25s R1W.

A Fir 12" dia. for closing cor. of secs. 3 and 4, I mark CC T26S R1W on S.; S3 on E.; and S4 on W. side, with 3 notches on E. and W. sides, from which

A Fir 14" dia., bears S.25°E., 36 lks. dist. mkd. T26S R1W S3 BT.

A Fir 14" dia., bears S.71°W., 18 lks. dist. mkd. T26S R1W S4 BT.

Fd Orig. Corner tree & 2 BTs B Shaner, 12/1964 CS 51/281-3 (added 10/16/2018)

Dennis Gaylord, U.S. Forest Service (Deputized by the County) - Sept. 1977 - C.S. File 59/40-11

Found - Orig. 12" now 16" D.Fir corner tree. Has been previously opened on the S. and W. sides. Has a healed scar on the E. side. Fragmentary scribing is visible on the opened face and on the removed pieces of wood (in reverse). There are 3 healed hacks on the E. and W. sides at chest height.

Orig. 14" now 31" D.Fir, bears S.25°E., 30.2 ft. (Rec. 23.76 ft.) Orig. dist. to this BT could be 10 lks. in error. Has a healed scar.

Orig. 14" now 30" D.Fir bears S.71°W., 13.3 ft. (Rec. 11.88 ft.) Has faint sign of a healed scar.

Placed DCSO BT signs on both trees, which are healthy and in good condition.

I placed a Forest Service location sign on the E. and one on the W. side of the corner tree, mkd. "Corner Tree." One ft. S. of the corner tree, I SET a 2½" brass cap on a 1" I.P. mkd. County Surveyors Office 1977

W.C.
1.0' N
C.C. ↑
S 4 | S 3
T26S R1W

No new accessories. Corner lies 350 ft. West of the Williams Creek Trail.