

TOWNSHIP 26 RANGE 01 POINT IDENTIFIER # 417700

PRIMARY CORNER DESCRIPTION So. 1/4 Cor. for Sec. 33 only, T25-1

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO survey by Hezekiah H. Johnson, Deputy Surveyor, under Contract #721, dated May 1, 1900 - (DCSO records Vol. 8 Page(s) 3503)

Set a basalt stone 20x14x10 ins., 15" in the ground for ¼ sec. cor. marked ¼ on N. face, from which
A Dogwood 5" dia., bears N.20°W., 27 lks. dist. mkd. ¼ S33 BT.
A Maple 5" dia., bears S.15°W., 17 lks. dist. mkd. ¼ S4 BT.

GLO survey by Fred Mensch, Deputy Surveyor, under Contract #797, dated April 19, 1910 - (DCSO records Vol. 9 Page(s) 3574) (and duplicate pages 4079A/4080A, Vol. 10)

The ¼ sec. cor., which is a basalt stone 5x12x10 ins., above ground, firmly set, marked and witnessed as described by the surveyor general, bears S. 44 lks. I re-establish this cor. in its original position as the ¼ sec. cor. on S. bdy. sec.33, T25S R1W only, as follows;
Stone, above described, already set, from which
A Fir 36" dia., bears N.39°E., 18 lks. dist. mkd. ¼ S33 BT.
A Dogwood 5" dia., bears N.20°W., 27 lks. dist. mkd. ¼ S33 BT.
I obliterate marks on former bearing tree referring to sec. 4.