

TOWNSHIP 26 RANGE 01 POINT IDENTIFIER # 440100

PRIMARY CORNER DESCRIPTION So. 1/4 Cor. for Sec. 34 only

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GL0 survey by Fred Mensch, Deputy Surveyor, under Contract #797, dated April 19, 1910 - (DCSO records Vol. 10 Page(s) 4098)

Set a basalt stone 18x12x8 ins., 12" in the ground for 1/4 sec. cor. on S. bdy. of sec. 34, marked 1/4 on N. face, from which
A Fir 36" dia., bears N.32°E., 35 lks. dist. mkd. 1/4 S34 BT.
A Hemlock 12" dia., bears N.78°W., 24 lks. dist. mkd. 1/4 S34 BT.

Douglas Co. Surveyors Office - John M. Powell, and crew - Nov. 13, 1969 - C.S. File 54/94-44

Found - No trace of Corner stone.
36" D.Fir, now stump, N.32°E., 23.1 ft. shows good scar.
12" Hemlock now stob, N.78°W., 15.8 ft., scribe visible.

Set Brass cap at cor. mkd: County Surveyors Office
T 26 S R1W 1/4 S 34
T 27 S 1969

New BTs- 7" Hemlock N.47°E., 32.9 ft. mkd. 1/4 S34 CS BT.
8" Hemlock N.13°E., 30.0 ft. mkd. 1/4 S34 CS BT.
This corner lies 92.4 ft. E. of 1/4 cor. sec. 3, T27-1.