

TOWNSHIP 26 RANGE \_\_\_\_\_ POINT IDENTIFIER # 440200

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 27 & 34

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO survey by Fred Mensch, Deputy Surveyor - contract #797 dated April 19, 1910 - (DCSO records Vol. 10 Page(s) 4127)  
-----  
Set a basalt stone 18x12x6", 12" in the ground for ¼ sec. cor. mkd. ¼ on N face, from which  
    A fir, 36" dia., bears N.14°W., 19 lks., mkd: ¼ S27 BT.  
    A fir, 16" dia., bears S.7°E., 51 lks., mkd: ¼ S34 BT.

---

Howard Johnston - For: Roseburg Lumber - 10/31/1973 - C.S. 55/320  
-----  
Found - 8"x10"x10" stone.  
        36" fir, N.14°W., 19 lks., scribe visible.  
        12" fir, S.7°E., 51 lks. scribe visible (now a stump which has been pushed out of place by a cat)  
Set - 5/8"x30" IR along side the stone.  
New BT - 12" hemlock S.22°E., 81.5 ft. "¼ S34 BT"

---

1