

TOWNSHIP 26 RANGE 01 POINT IDENTIFIER # 440500

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 10 & 15

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO survey by Fred Mensch, Deputy Surveyor - contract #797 dated April 19, 1910 - (DCSO records Vol. 10 Page(s) 4132-3)

-----  
Set a basalt stone 15x10x6", 10" in the ground for ¼ sec. cor. mkd. ¼ on N face, from which

A fir, 5" dia., bears N.33°E., 8 lks., mkd: ¼ S10 BT.

A fir, 5" dia., bears S.64°E., 16 lks., mkd: ¼ S15 BT.

George Grubb - For: USFS - May 1981 - M87-65 A&B

-----  
Found - 11x9x5" basalt stone, firmly set, projecting 3" above the ground marked "¼" on the north face, and "+" on top. (record 15x10x6")

Set - At the exact corner point set a 2"x30" I.P. 24" in the ground in a 3 ft. dia. mound of stone with a 3" brass cap marked:

T 26 S R1W ¼ S10 S15 1981 LS 397.

New BTs- A 12" D.Fir bears S.54°W., 14.6 ft. scribed ¼ S15 BT

A 13" hemlock bears N.63°W. 37.0 ft scribed "¼ S10 BT"

Set original corner stone alongside in mound of stone.