

TOWNSHIP 26 RANGE 01 POINT IDENTIFIER # 440600

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 3 & 10

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO survey by Fred Mensch, Deputy Surveyor - contract #797 dated April 19, 1910 - (DCSO records Vol. 10 Page(s) 4135)

Set a conglomerate stone 15x12x8", 10" in the ground for ¼ sec. cor. mkd. ¼ on N face, from which
A fir, 24" dia., bears N.78°E., 26 lks., mkd: ¼ S3 BT.
A fir, 20" dia., bears S.12°W., 52 lks., mkd: ¼ S10 BT.

Dennis Gaylord, USFS & Deputy Co. Surveyor - Roland Simshauser, witness - Jan. 26, 1978 - C.S. File 59/46-8

Found - Stone, set solidly in place, mkd. "¼" on the north face, stone measures 14x11x7".
24" now 50" D.Fir bears N.78°E., 17.6 ft. There are 3 small axe marks on the bark facing the corner & a healed blaze on the south side of the tree.
A 20" now 35" D.Fir snag bears S.12°W., 34.3 ft. has a healed blaze which faces corner.
Set - Moving the orig. corner stone aside, I set in its place a 2½" BC on a 1" I.P. mkd. County Surveyors Office T26S R1W ¼ S3 S10 1970
I bury the corner stone alongside.
New BT - A 29" D.Fir bears S.16°30'W., 94.9 ft scribed "¼ S10 CS BT" on a double blaze.
Corner lies 250 ft. north of power line.