

TOWNSHIP 26 RANGE 01 POINT IDENTIFIER # 478100

PRIMARY CORNER DESCRIPTION Sec. Cor. for 2 & 3 only, T27-1

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by Homer D. Angell, Deputy Surveyor, under Contract #746, dated May 5, 1902 - (DCSO records Vol. 11 Page(s) 4790)

Set a basalt stone 15x8x8 ins., 10" in ground for cor. of secs. 2, 3, 34 and 35, marked with 2 notches on E. and 4 notches on W. edges, from which
A Hemlock 12" dia., bears N.36°E., 27 lks. dist. mkd. T26S R1W S35 BT.
A Hemlock 28" dia., bears S.67°E., 32 lks. dist. mkd. T27S R1W S2 BT.
A Hemlock 28" dia., bears S.70°W., 37 lks. dist. mkd. T27S R1W S2 BT.
A Hemlock 28" dia., bears N.82°W., 59 lks. dist. mkd. T26S R1W S34 BT.

GLO survey by Fred Mensch, Deputy Surveyor, under Contract #797, dated April 19, 1910 - (DCSO records Vol. 10 Page(s) 4094 and 4098)

(Page 4094)
The cor. of secs. 2, 3, 34 and 35, firmly set, marked and witnessed as described by the surveyor general.
(Page 4098)
The old cor., which I re-establish as the cor. of secs. 2 and 3, T27S R1W only, by obliterating marks on bearing trees referring to secs. 34 and 35.

Douglas Co. Surveyors Office - John M. Powell, and crew - Nov. 1969 - C.S. File 54/94-32

Found - Mound of stone at corner, stone mkd. with notches, not found.
28" Hemlock, now snag, S.67°E., 21.1 ft. scribe visible.
28" now 38" Hemlock S.70°W., 24.4 ft. scribe visible.

Set Brass cap at cor. mkd: County Surveyors Office
T26S R1W S 34
T27S S 3 | S 2
1969

New BT - 40" Hemlock S.62°E., 41.0 ft. mkd. T27S R1W S2 CS BT
This corner lies 85.0 ft. E. of cor. secs. 34 & 35, T26-1.