

TOWNSHIP 26 RANGE 01 POINT IDENTIFIER # 500100

PRIMARY CORNER DESCRIPTION Sec. Cor. for 34 & 35 (South)

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

GL0 survey by Fred Mensch, Deputy Surveyor, under Contract #797, dated April 19, 1910 - (DCSO records Vol. 10 Page(s) 4097-98)

-----  
A Fir 48" dia., for cor. of secs. 34 and 35, I mark T26S S35 on NE.; and R1W S34 on NW. side, with 2 notches on E. and 4 notches on W. side, from which  
    A Hemlock 5" dia., bears N.31°E., 4 lks. dist. mkd. T26S R1W S35 BT.  
    A Fir 40" dia., bears N.25°W., 15 lks. dist. mkd. T26S R1W S34 BT.

Douglas Co. Surveyors Office - John M. Powell, and crew - Nov. 6, 1969 - C.S. File 54/94-31

-----  
Found - 48" D.Fir Corner tree, good scars.  
        5" now 6" Hemlock N.31°E., 2.6 ft. scribe visible.  
        40" now 46" D.Fir N.26°W., 9.9 ft. shows good scar.  
Set Brass cap on N. side of Corner tree mkd:  
        County Surveyors Office  
        T26S           R1W    S 34 | S 35  
        T27S           1969    S    2  
New BT - 7" Hemlock N.75°E., 25.6 ft. mkd. T26S R1W S35 CS BT.  
This corner lies 85.0 ft. W. of cor. to secs. 3 & 3, T27-1.