

TOWNSHIP 26 RANGE 01 POINT IDENTIFIER # 500200

PRIMARY CORNER DESCRIPTION Cor Secs. 26, 27, 34 & 35

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO survey by Fred Mensch, Deputy Surveyor - contract #797 dated April 19, 1910 - (DCSO records Vol. 10 Page(s) 4114-5)  
-----

Set a basalt stone 15x8x8", 10" in the ground for cor. of secs. 26, 27, 34, & 35 mkd with 1 notch on S & 2 notches on E edge, from which

- A fir, 48" dia. bears N.71°E. 24 lks. mkd: T26S R1W S26 BT
- A hemlock, 24" dia., bears S.3°E., 50 lks., mkd: T26S R1W S35 BT.
- A fir, 24" dia. bears S.20°W. 69 lks. mkd: T26S R1W S34 BT
- A fir, 7" dia. bears N.25°W., 40 lks. mkd: T26S R1W S27 BT

Dennis Gaylord, USFS - Douglas Co. Surveyors Office -  
Witness: James Davis - Sept. 13, 1978 - C.S. File 60/17-4  
-----

Found - Orig. corner stone, marked "X" on top and with 2 grooves on the East face and one notch on the South edge, is firmly set in the ground. The stone measures 5x6x12".

- A 75" D.Fir bears S.71°E., 15.84 ft. has a healed blaze.
- A 37" Hemlock bears S.3°E., 33.0 ft. some scribing is visible on a nearly healed blaze.
- A 32" Shasta Fir snag bears S.20°W., 45.54 ft. scribing visible on a partly healed blaze, T26S R1W S34 BT"
- A 11" D.Fir bears N.25°W., 22.8 ft. Has a healed blaze. (This tree is crooked, dist. is to base of tree.) Rec. dist. is 26.4 ft.

Set - Referencing the corner stone, I SET it aside and in its place I set a 1½" I.P. with a 2½" brass cap attached, stamped: County Surveyors Office T26S R1W S27 S26 S34 S35 1978". I bury the corner stone alongside the Iron pipe.

New BT - A 12" Shasta Fir bears S.43°30'W., 58.9 ft. scribed "T26S R1W S34 CS BT" on a double blaze.

Placed County BT signs on all 5 BTs.