

PRIMARY CORNER DESCRIPTION Cor. Secs. 10, 11, 14, & 15

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by Fred Mensch, Deputy Surveyor - contract #797 dated April 19, 1910 - (DCSO records Vol. 10 Page(s) 4120)

Set a basalt stone 18x10x6", 12" in the ground for cor. of secs. 10, 11, 14, & 15 mkd with 4 notches on S & 2 notches on E edge, from which

- A fir, 24" dia. bears N.87°E. 25 lks. mkd: T26S R1W S11 BT
- A fir, 24" dia. bears S.24°E. 23 lks. mkd: T26S R1W S14 BT
- A fir, 18" dia. bears S.87°W. 14 lks. mkd: T26S R1W S15 BT
- A fir, 36" dia. bears N.65°W. 83 lks. mkd: T26S R1W S10 BT

Dennis Gaylord, USFS & Deputy Douglas Co. Surveyor - Randal Lopez & Jim Talburt, Witnesses - Feb. 1978 - C.S. 59/46-10

Found - Orig. corner stone firmly set in the ground, measures 18x9x7" & is marked "X" on top & has 4 notches on the South edge and 2 notches on the East edge.

Orig. BT to the SW is down & decayed. Stump hole bears S.87°W., 9.24 ft.

Orig. 38" now 37" D.Fir snag bears N.65°W., 54.8 ft. (Rec. N.63°W) Axe marks on bark where blaze was.

Orig. 24" now decayed Fir snag bears S.21°E., 14.48 ft. (Rec. S.24°E., 15.18 ft.) Has axe marks on bark where blaze was.

Orig. 24" now decayed D.Fir snag bears N.87°E., 16.5 ft. Axe marks on bark where blaze was.

Set - Moving the corner stone aside, I SET in it's place a 2½" B.C. on a 1" I.P. stamped: County Surveyors Office T26S R1W S10 S11 S15 S14 1978. I bury the corner stone alongside.

New BTs- A 30" D.Fir bears N.79°30'E., 40.1 ft. scribed "T26S R1W S 11 CS BT" on a double blaze.

A 26" D.Fir bears N.64°W., 41.0 ft. scribed "T26S R1W S10 CS BT on a double blaze.

A 21" D.Fir bears S.70°W., 7.3 ft. scribed "T26S R1W S15 CS BT on a double blaze.

A 16" D.Fir bears S.9°E., 24.2 ft. scribed "T26S R1W S14 CS BT on a double blaze.