

TOWNSHIP 26 RANGE 01 POINT IDENTIFIER # 500600

PRIMARY CORNER DESCRIPTION Cor. Secs. 2, 3, 10, & 11

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO survey by Fred Mensch, Deputy Surveyor - contract #797 dated April 19, 1910 - (DCSO records Vol. 10 Page(s) 4122)

Set a basalt stone 16x10x8", 11" in the ground for cor. of secs. 2, 3, 10, & 11 mkd with 5 notches on S & 2 notches on E edge, from which

- A fir, 20" dia. bears N.7°E., 169 lks. mkd: T26S R1W S2 BT
- A fir, 36" dia. bears S.5°E., 79 lks. mkd: T26S R1W S11 BT
- A fir, 30" dia. bears S.50°W. 87 lks. mkd: T26S R1W S10 BT
- A fir, 36" dia. bears N.31½°W. 73 lks. mkd: T26S R1W S3 BT

Dennis Gaylord, USFS & Deputy Co. Surveyor - Roland Simshauser, witness - Jan. 19, 1978 - C.S. File 59/46-6

Found - Stone, 16x10x8" & marked "X" on top, solidly set in the ground & covered with duff. 5 grooves on the "J" (broken SE face) & 2 grooves on the east face
A 51" D.Fir bears N.30°W., 43.7 ft. (Rec. N.31½°W., 48.18 ft. scribing visible on previously opened blaze "26S R1W S3 B"
A 47" D.Fir bears N.7°E., 112.1 ft. (Rec. N.7°E., 111.54 ft.)
BTs to the south are gone without a trace.
Placed County BT signs on all 5 bearing trees.

Set - Moving orig. corner stone aside, I SET in it's place a 2½" Brass cap on a 1" I.P. mkd County Surveyors Office T26S R1W S3 S2 1978.
S10 S11

I bury orig. corner stone alongside.
New BTs- A 11" D.Fir bears N.84°W., 9.1 ft. scribed "T26S R1W S3 CS BT" on a double blaze.
A 14" D.Fir bears S.17½°W., 31.8 ft. scribed "T26S R1W S10 CS BT" on a double blaze.
A 17" D.Fir bears S.31°E., 32.3 ft. scribed "T26S R1W S11 CS BT" on a double blaze.

Corner lies on a steep southeast slope approx. 200 ft. NW of the old North Umpqua Road.

James M. Stanley, ODOT - Sept/Nov. 2007 - St. Hwy 138-011P

Fd. 2½" brass cap stamped "COUNTY SURVEYORS OFFICE T26S R1W S32 S2 S0 S11 1978" (10-2-07)
N. 613893.547
E. 4311384.668