

TOWNSHIP 26 RANGE 01 POINT IDENTIFIER # 540200

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 26 & 35

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO survey by Fred Mensch, Deputy Surveyor - contract #797 dated April 19, 1910 - (DCSO records Vol. 10 Page(s) 4115)

Set a basalt stone 12x8x6", 8" in the ground for ¼ sec. cor. mkd. ¼ on N face, from which

A fir, 9" dia., bears N.75°E., 14 lks., mkd: ¼ S26 BT.

A fir, 18" dia., bears S.35°E., 27 lks., mkd: ¼ S35 BT.

Douglas Co. Surveyors Office - John Powell - 8/1971 - C.S. File 54/94

Not found, call of 7.71 chs East of cor. probably destroyed by old partial cut. There are several E-W blazed lines, also a couple of N-S blazed lines.

Douglas Co. Surveyors Office - Clell Goodwin - Vic Cangie - Lenora Ladig - Sept. 30, 1975 - C.S. File 57/36-12

Found - 6x4x5" stone scribed ¼ on north face from which a 18" stump with visible scribe bears S.35°E., 17.8 ft. and a rotted 10" stump bears N.75°E., 9.2 ft.

New - We set at the corner a 1½"x30" I.P. with brass cap stamped:

T26S R1W
DOUGLAS CO. SURVEYOR ¼ $\frac{S\ 26}{S\ 35}$
1975

We set the stone alongside from which:

A 15" Hemlock scribed "¼ S35 CS BT" in a double blaze bears S.4½°E., 33.4 ft.

A 18" Fir scribed "¼ S26 CS BT" in a double blaze bears N.23½°W., 74.3 ft

Compass declination 20° East

NOTE - Corner lies approx 50, south of road to rock pit and on west edge of clear cut.