

TOWNSHIP 26 RANGE 01 POINT IDENTIFIER # 500240

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 26 & 27

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO survey by Fred Mensch, Deputy Surveyor - contract #797 dated April 19, 1910 - (DCSO records Vol. 10 Page(s) 4116)

Set a basalt stone 15x10x6", 10" in the ground for ¼ sec. cor. mkd. ¼ on W face, from which
A fir, 36" dia., bears N.47°E., 10 lks., mkd: ¼ S26 BT.
A fir, 16" dia., bears N.50°W., 14 lks., mkd: ¼ S27 BT.

Dennis Gaylord, USFS & Deputy Co. Surveyor - Roland Simshauser, witness - Jan. 19, 1978 - C.S. File 59/46

Found - A 36" D.Fir stump with partly healed blaze bears N.47°E., 6.6 ft. scribing visible "4 S 26". Stump has been slightly disturbed during logging.
BT to the NW is gone.
Set - 2½" brass cap on a 1" I.P. stamped County Surveyors Office T26S R1W ¼ S27 S26 1978". Used only remaining BT stump as reference.
New BT - A 34" D.Fir bears S.69½°E., 211.0 ft. scribed "¼ S26 CS BT" on a double blaze.
Set - A 5/8" Re-bar in a 36" Fir stump, re-bar bears S.34°W., 28.9 ft. Placed Co. BT signs on all 3.
Corner falls in skid trail.