

TOWNSHIP 26 RANGE 01 POINT IDENTIFIER # 540300

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 23 & 26

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO survey by Fred Mensch, Deputy Surveyor - contract #797 dated April 19, 1910 - (DCSO records Vol. 10 Page(s) 4117)

Set a basalt stone 12x10x5", 8" in the ground for ¼ sec. cor. mkd. ¼ on N face, from which
 A cedar, 12" dia., bears N.67°E., 21 lks., mkd: ¼ S23 BT.
 A fir, 30" dia., bears S.30°E., 15 lks., mkd: ¼ S26 BT.

Dennis Gaylord, USFS & Deputy Co. Surveyor - Witness: Travis Worthen - Sept 1977 - C.S. File 59/40-14

Found - Stone 12x8x4" set solidly in the ground. marked "X" on top & "1/4" on the north face.
 Orig. 30" now 36" D.Fir bears S.33°30'E., 9.9 ft. (Rec. S.30°E., 9.9 ft.) Has a healed scar.
 Orig. 12" now 20" Red Cedar bears N.71°E., 13.86 ft. (Rec. N.67°E., 13.86 ft.) Has a healed scar.
 Placed county BT signs on both trees, which are alive & well.
Set - Removing the stone, I set in it's place a 2½" Brass cap on 1" IP. B.C. stamped County Surveyors Office T26S R1W ¼ S23 S26 1977. I buried the corner stone alongside the I P.
No new accessories. Corner lies 100 ft. east of F.S. Rd. #2616D