

TOWNSHIP 26 RANGE 01 POINT IDENTIFIER # 557700

PRIMARY CORNER DESCRIPTION Sec. Cor. for 34 & 25 only, T25-1

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO survey by Hezekiah H. Johnson, Deputy Surveyor, under Contract #721, dated May 1, 1900 - (DCSO records Vol. 8 Page(s) 3501)

Set a basalt stone 20x10x5 ins., 15" in the ground for cor. secs. 2, 3, 34 and 35 marked with 2 notches on E. and 4 notches on W. faces, from which

- A Fir 60" dia., bears N.22°E., 49 lks. dist. mkd. T25S R1W S35 BT.
- A Cedar 7" dia., bears S.65°E., 48 lks. dist. mkd. T25S R1W S2 BT.
- A Cedar 16" dia., bears S.65°W., 87 lks. dist. mkd. T25S R1W S3 BT.
- An Alder 7" dia., bears N.55°W., 69 lks. dist. mkd. T25S R1W S34 BT.

GLO survey by Fred Mensch, Deputy Surveyor, under Contract #797, dated April 19, 1910 - (DCSO records Vol. 9 Page(s) 3572) and duplicate Pg. 4080)

The cor. of secs. 2, 3, 34 and 35, which is a basalt stone 5x10x5 ins. above ground, firmly set, mkd. and witnessed as described by the surveyor general. I re-establish this cor. as the cor. of secs. 34 and 35, T25S R1W only, by obliterating marks on bearing trees referring to T26S.