

PRIMARY CORNER DESCRIPTION Sec. Cor. for 1 & 2 only, T27-1

Alias	Description
Alias	Description
Alias	Description
Alias	Description

GL0 survey by Homer D. Angell, Deputy Surveyor, under Contract #746, dated May 5, 1902 - (DCSO records Vol. 11 Page(s) 4791)

-
- Set a basalt stone 15x10x5 ins., 10" in ground for cor. of secs. 1, 2, 35 and 36, marked with 1 notch on E. and 5 notches on W. edges, from which
- A Fir 16" dia., bears N.50°E., 78 lks. dist. mkd. T26S R1W S36 BT.
 - A Fir 16" dia., bears S.61°E., 54 lks. dist. mkd. T27S R1W S1 BT.
 - A Fir 12" dia., bears S.35½°W., 57 lks. dist. mkd. T27S R1W S2 BT.
 - A Fir 20" dia., bears N.69°W., 75 lks. dist. mkd. T26S R1W S35 BT.

GL0 survey by Fred Mensch, Deputy Surveyor, under Contract #797, dated April 19, 1910 - (DCSO records Vol. 10 Page(s) 4094-95 and 4096-97) GL0 survey by Fred Mensch, Deputy Surveyor, under Contract #797, dated April 19, 1910 - (DCSO records Vol. 10 Page(s) 4094-95 and 4096-97)

-
- (Pages 4094-95)
The cor. of secs. 1, 2, 35 and 36, which is a basalt stone 5x10x5 ins., above ground, firmly set, marked and witnessed as described by the surveyor general.
- (Pages 4096-97)
The old cor. of secs. 1, 2, 35 and 36, which I re-establish as the cor. of secs. 1 and 2, T27S R1W only, by obliterating marks on bearing trees referring to secs. 35 and 36.

Douglas Co. Surveyors Office - John M. Powell, and crew - Oct. 27, 1969 - C.S. File 54/94-16

-
- Found - Unrecorded Alum. cap at cor. mkd. "U.S.P.C. Prop. Cor. RE 4287 35 S2|S1".
Possible SE. BT, down and out of place, laying on face.
20" Hemlock S.63°E., 52.6 ft. mkd. "S1 BT".
- New BT - 18" Hemlock S.47°E., 62.0 ft. mkd. T27S R1W S1 CS BT.
- This corner lies on E. side of cut unit, on top of ridge, running N. 49.5 ft. West of section corner to secs. 35 & 36 only, T26-1W.

continued next page

PRIMARY CORNER DESCRIPTION Sec. Cor. for 1 & 2 T27-1W only,

Alias	Description
_____	_____
Alias	Description
_____	_____
Alias	Description
_____	_____
Alias	Description
_____	_____

BLM dependent resurvey by Jasper M. Sams & Donovan C. Harris, Cadastral Surveyors, under Group No. 747, surveyed June/Aug. 1971 - (DCSO records Vol. 35 Page(s) 14572)

The cor. of secs. 1 & 2 only, on the N. bdy. Of the Tp., perpetuated by Shrum, with an iron pipe, 1" dia., firmly set, protruding 16" above the ground, with aluminum cap mkd.

U.S.P.C.
35

2 | 1
PROP. COR.
RE. 4287

from which the remains of the original bearing tree:
A root hole, bears S.61°E., 54 lks., alongside of which is lying a fir, 24" diam., with scribe marks "27S 1W S1" visible on partially healed blaze.
And a bearing tree tagged by RE. 4287:
A Hemlock, 20" dia., bears S.53°E., 79 lks., with metal tag attached, marked "S1 BT".
And a bearing tree by DCSO in 1969:
A Hemlock, 16" diam., bears S.43°E., 93 lks., scribed "T27S R1W S1 CS BT" on a partially healed blaze.
Add the marks BLM 1971 to aluminum cap.

Fd. & used on U.S. Forest Service by Ronald Quimby and Romaso Ware, per M 79-55, dated August 1980

Kris DeGroot - USFS - 8/2008 - C.S. File 65/63-33A&B

Found - A 1" iron post, firmly set, projecting 18" above the ground with a 2½" dia. aluminum cap (Note: with a stone buried on the north side)
From which a bearing tree by Shrum at an unknown date:
Was 20" now 21" ± 25 ft. tall broken, fir snag bears S.63°E., 52.6 ft. with scribing S1" visible in partially healed face.
And a bearing tree by Powell in 1969:
Was 18" now 19" Hemlock bears S.47°E., 62.0 ft. with illegible scribing visible in partially healed face.
And a reference monument:
A 1 ¼" iron post exposed 18" above the ground with a 2½" diam. brass cap stamped; "County Surveyors Office T26S R1W S35 S36 S1 T27S 1969" bears East, 49.05 ft. (Rec. East, 49.5 ft. 1969) with a stone buried on the south side.
New BT - A 10" D. Fir bears S.50°30'W., 14.7 ft. which I scribe "T27S R1W S2 BT" on double face. cont.

TOWNSHIP 26 RANGE 01 POINT IDENTIFIER # 578100

PRIMARY CORNER DESCRIPTION Sec. Cor. for 1 & 2 only, T27-1

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

All new bearing trees have double blazed faces with a brass washer stamped "PLS 1941" nailed into the lower blaze. Bearings are taken to the center of the tree at the root crown and distances are measured to an aluminum nail in the root crown at the side and center of the tree. All bearing trees have a 6" red band painted around the tree and the blazed face painted red and Bearing Tree and USFS Land Survey Monument sign nailed to the tree.
Corner renewal date: August 5, 2008
Party Chief: Lester Fanning, PLS 2664
Witnesses: Scott McCurdy, and Rick Sanford
Warren Knight Staff Compass -- declination 18°E