

TOWNSHIP 26 RANGE 01 POINT IDENTIFIER # 600100

PRIMARY CORNER DESCRIPTION Sec. Cor. for 35 & 36 only (South)

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

GL0 survey by Fred Mensch, Deputy Surveyor, under Contract #797, dated April 19, 1910 - (DCS0 records Vol. 10 Page(s) 4096)

-----  
Set a conglomerate stone 16x10x5 ins., 11" in the ground for cor. of secs. 35 & 36, marked with 1 notch on E. and 5 notches on W. edge, from which  
A Fir 20" dia., bears N.76°E., 27 lks. dist. mkd. T26S R1W S36 BT.  
A Fir 9" dia., bears N.87°W., 10 lks. dist. mkd. T26S R1W S35 BT.

Douglas Co. Surveyors Office - John M. Powell, and crew - Oct. 1969 - C.S. File 54/94-17

-----  
Found - 16x10x5 stone, firmly set, mkd. with 1-5 notches.  
20" Fir now down, N.76°E., 17.8 ft. broken face and scribe marks visible.  
9" Fir now down, N.87°W., 6.6 ft. tree opened, pitched over, scribe visible.

Set Brass cap at cor. mkd: County Surveyors Office  
T 26 S R 1 W  
S 35 | S 36  
S 1  
T27S

New BTs- 30" D.Fir N.74°E., 22.0 ft. mkd. T26S R1W S36 CS BT  
30" D.Fir N.11°E., 22.4 ft. mkd. T26S R1W S36 CS BT.  
This corner lies in E. edge of clear cut unit, 49.5 ft. E. of cor. of secs. 1 & 2, T27-1W.