

TOWNSHIP 26 RANGE 01 POINT IDENTIFIER # 600140

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 35 & 36

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO survey by Fred Mensch, Deputy Surveyor - contract #797 dated April 19, 1910 - (DCSO records Vol. 10 Page(s) 4103)

Set a basalt stone 16x8x5" 11" in the ground for ¼ sec. cor. marked ¼ on W face, from which

A fir, 20" dia., bears N.30°E., 35 lks., mkd: ¼ S36 BT.

A fir, 36" dia., bears S.20°W., 13 lks., mkd: ¼ S35 BT.

Douglas Co. Surveyors Office - A. Victor Cangie - Peter L. Earle - 5/27/1976 - C.S. File 59/15-10

Found - 20" fir stump that bears N.30°E., 23.1'. Scribing "¼ 36 BT" visible on unhealed blaze.

36" now 40" fir that bears S.20°W., 8.6' bearing healed blaze. We open and find "BT", alive and well.

At corner determined from intersection of dist. and bearings of above BTs we find no trace of orig. basalt stone.

Set - A 1x30" IP w/brass cap stamped: Douglas County Surveyor
T26S R1W
S35|S36
¼ 1976

New BT - 9" Hemlock bears N.21°E., 31.0' marked "¼ S36 CS BT" in a double blaze.

Note - Corner is approx. 300' East of Road #2616.
Compass dec. 20° East.