

TOWNSHIP 26 RANGE 01 POINT IDENTIFIER # 600200

PRIMARY CORNER DESCRIPTION Cor. Secs. 25, 26, 35, & 36

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by Fred Mensch, Deputy Surveyor - contract #797 dated April 19, 1910 - (DCSO records Vol. 10 Page(s) 4103-4)

Set a basalt stone 15x8x6", 10" in the ground for cor. of secs. 25, 26, 35, & 36 mkd with 1 notch on E & 1 notch on S edge, from which

A fir, 24" dia., bears N.22½°E., 40 lks., mkd: T26S R1W S25 BT.

A fir, 16" dia., bears S.67½°E., 29 lks., mkd: T26S R1W S36 BT.

A hemlock, 12" dia., bears S.54°W., 41 lks., mkd: T26S R1W S35 BT.

A fir, 20" dia. bears N.25°W. 30 lks. mkd: T26S R1W S26 BT

Dennis Gaylord, USFS - Douglas Co. Surveyors Office -
Witness: James Davis - Aug. 31, 1978 - C.S. File 60/11-35

Found - Orig. corner stone, 4x7x12" & marked with one notch on the east edge and one notch on the south edge, is firmly set in the ground.

A 26" D.Fir bears N.24°E., 25.8 ft. (Rec. N.22½°E., 26.4 ft.) scribing visible on previously opened blaze.

A 36" D.Fir bears N.22½°W., 19.3 ft. (Rec. N.25°W., 19.8 ft.) Has a healed blaze which has been previously partially opened.

A 24" Hemlock bears S.51½°W., 20.2 ft. (Rec. S.54°W., 27.06 ft. Has a healed scar. 10 lk. error in record measurement to this BT.

A 28" D.Fir bears S.68°E., 19.4 ft. (Rec. S.67½°E., 19.14 ft.) Has a previously opened blaze with visible scribing. (This tree is not too healthy)

Set - Referencing the corner stone, I move it aside and set in it's place a 1½" Iron pipe with a 2½" brass cap marked "County Surveyors Office T26S R1W S26 S25 S35 S36 1978". I bury the corner stone alongside the iron pipe.

New BTs- A 19" D.Fir bears S.60°E., 43.9 ft. scribed "T26S R1W S36 CS BT" on a double blaze.

Placed County BT signs on all 5 BTs.