

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 25 & 26

Alias	Description

GLO survey by Fred Mensch, Deputy Surveyor - contract #797 dated April 19, 1910 - (DCSO records Vol. 10 Page(s) 4105)

Set a basalt stone 14x10x7", 9½" in the ground for ¼ sec. cor. mkd. ¼ on W face, from which
 A fir, 15" dia., bears S.30°E., 17 lks., mkd: ¼ S25 BT.
 A hemlock, 10" dia., bears N.46°W., 10 lks., mkd: ¼ S26 BT

Douglas Co. Surveyors Office - Stephen Flause - Terrie Plouff - Karen Mosley - April 23, 1981 - C.S. File 61/19-46

Found - A stone, 11x10x6" lying loose on ground surface, possibly orig. 14x10x7" corner stone, decayed by weather scaling, no markings visible.
 An orig. 15" fir, now a 18" stump approx 4.5 ft. tall bears S.30°E., 11.2 ft. Tree has good evidence of a healed blaze, no scribing visible.
 An orig. 10" hemlock, now 12" stump approx. 6.6 ft. tall bears N.45°W., 6.6 ft. Tree has scribing 6 B visible on a partially healed opened blaze.

Set - The position of the found stone is accepted as the corner position. Location of stone is referenced out and the stone is removed to be replaced by a DCSO 2½" brass cap on a 1" x 30" I.P. marked: "Douglas County Surveyor T26S R1W ¼ S26 S25 1981" Possible orig. stone is reset on the west side of the brass cap monument.

New BTs- An 11" DBH yew tree bears N.17°E., 38.4 ft. scribed "¼ S25 CS BT" on dead barkless wood facing the corner.
 An 8" DBH W.Fir bears S.21°W., 58.4 ft. scribed "¼ S26 CS on a double blaze.
 A 7" hemlock bears N.73°W., 50.8 ft. scribed "¼ S26 CS BT" on a double blaze.
 No other suitable trees were available. All trees are tagged with DCSO BT tags.