

TOWNSHIP 26 RANGE 01 POINT IDENTIFIER # 600400

PRIMARY CORNER DESCRIPTION Cor. Secs. 13, 14, 23, & 24

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO survey by Fred Mensch, Deputy Surveyor - contract #797 dated April 19, 1910 - (DCSO records Vol. 10 Page(s) 4107)

Point for cor. of secs. 13, 14, 23, & 24, falls on a basalt rock in place, 16x30x16", above ground on which I cut a cross (x) at exact cor. point, with 1 notch E & 3 notches S of cross, from which

- A fir, 18" dia. bears N.63°E. 14 lks. mkd: T26S R1W S13 BT
- A fir, 30" dia. bears S.24°E. 14 lks. mkd: T26S R1W S24 BT
- A fir, 40" dia. bears S.62°W., 5 lks. mkd: T26S R1W S23 BT
- A fir, 18" dia. bears N.14°W. 25 lks. mkd: T26S R1W S14 BT

Dennis Gaylord, USFS - Douglas Co. Surveyors Office -
Witness: James Davis - Sept. 14, 1978 - C.S. File 60/17-7

Found - Orig. corner stone is set firmly in place. Stone is marked "X" on top and 3 grooves on the South. Stone measures 24x28x12" above ground.

Orig. 40" Fir is now a burned & decayed stump. Stump bears S.62°W. 6.0 ft. scribing visible, "6S T S 3 BO"

No other BTs remaining.

Set - I am unable to move corner stone due to its size, So I SET a 1½" iron pipe with a 2½" brass cap, stamped: County Surveyors Office T26S R1W S14 S13 S23 S24 WC 0.4' S 1978", alongside the corner stone, 0.4 ft. North of the "X" mark on the corner stone.

- New BTs-
- A 19" D.Fir bears S.67°E., 37.5 ft. scribed "T26S R1W S24 CS BT" on a double blaze.
 - A 14" D.Fir bears N.56°E., 33.9 ft. scribed "T26S R1W S13 CS BT" on a double blaze.
 - A 19" D.Fir bears N.49°W., 17.0 ft. scribed "T26S R1W S14 CS BT" on a double blaze.
 - A 13" D. Fir bears S.6°W., 32.4 ft. scribed "T26S R1W S23 CS BT" on a double blaze.

All new accessories are referenced to the "X" mark on the corner stone. Placed County BT signs on all BTs.