

TOWNSHIP 26 RANGE 01 POINT IDENTIFIER # 600500

PRIMARY CORNER DESCRIPTION Cor. Secs. 11, 12, 13, & 14

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO survey by Fred Mensch, Deputy Surveyor - contract #797 dated April 19, 1910 - (DCSO records Vol. 10 Page(s) 4109)

Set a conglomerate stone 18x18x18", 12" in the ground for cor. of secs. 11, 12, 13, & 14 mkd with 1 notch on E & 4 notches on S edge, from which

A hemlock, 9" dia., bears N.69°E., 48 lks., mkd: T26S R1W S12 BT.

A maple, 8" dia. bears S.34°E. 9 lks. mkd: T26S R1W S13 BT

A fir, 48" dia. bears S.24°W., 8 lks. mkd: T26S R1W S14 BT

A cedar, 7" dia., bears N.82°W., 23 lks., mkd: T26S R1W S11 BT.

Dennis Gaylord, USFS - Douglas Co. Surveyors Office -
Witness: James Davis - Sept. 12, 1978 - C.S. File 60/17-2

Found - Orig. corner stone set firmly in place. Stone is marked "+" on top and has one groove on the east and 4 grooves on the south. Stone measures 12x13x17".

A 27" Fir snag bears S.24°W., 5.28 ft. scribing visible, "T26S R1W-14 BT".

No other BTs remaining.

Set - Moving the cor stone aside, I SET in its place a 1½" IP with a 2½" brass cap attached stamped: County Surveyors Office T26S R1W S11 S12 S14 S13 1978.

New BTs- A 12" D.Fir bears S.62°30'E., 29.1 ft. scribed "T26S R1W S13 CS BT" on a double blaze.

A 6" D.Fir bears West, 42.4 ft. scribed "T26S R1W S14 CS BT" on a double blaze.

A 11" B. Fir bears N.34°W., 26.7 ft. scribed "T26S R1W S11 CS BT" on a double blaze.

A 12" D.Fir bears N.19°30'E., 22.6 ft. scribed "T26S R1W S12 CS BT" on a double blaze.

Placed County BT signs on all BTs. I bury corner stone alongside Iron Pipe.