

TOWNSHIP 26 RANGE 01 POINT IDENTIFIER # 600540

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 11 & 12

Alias	Description
_____	_____
_____	_____
_____	_____
_____	_____

GLO survey by Fred Mensch, Deputy Surveyor - contract #797 dated April 19, 1910 - (DCSO records Vol. 10 Page(s) 4110)

Set a basalt stone 12x8x6", 8" in the ground for ¼ sec. cor. mkd. ¼ on W face, from which

A cedar, 10" dia., bears S.84°E., 16 lks., mkd: ¼ S12 BT.

A fir, 48" dia., bears S.8°W., 5 lks., mkd: ¼ S11 BT.

Douglas Co. Surveyors Office - Milo E. Godfrey - Vernon Tracy & Clete Putnam - June 8, 1962 - C.S. File 52/77-8

Found - Rock set by Mensch, in place, Mkd: "¼" on W face. Cedar S.84°E. 10.6 ft., down & dead, good scribing "¼ S12 BT" visible on old face.

Fir, now 55", S.8°W., 38.9 ft., has been opened previously & good scribing "S" visible on portion of old face.

Alongside Rock at Cor. Set Brass Cap Mkd:
County Surveyors Office, 1962
T26S R1W S11|S12

New BTs- 5" D.Fir N.46°W. 17.6 ft. Mkd: ¼ S11 CS BT.

5" D.Fir N.64°E. 26.6 ft. Mkd: ¼ S12 CS BT.