

TOWNSHIP 26 RANGE 01 POINT IDENTIFIER # 640100

PRIMARY CORNER DESCRIPTION So. 1/4 Cor. for Sec. 36 only

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GL0 survey by Fred Mensch, Deputy Surveyor, under Contract #797, dated April 19, 1910 - (DCSO records Vol. 10 Page(s) 4095-96)

Set a basalt stone 12x8x8 ins., 8" in the ground for ¼ sec. cor. on S. bdy. of sec. 36, marked ¼ on N. face, from which
A Fir 10" dia., bears N.6°E., 57 lks. dist. mkd. ¼ S36 BT.
A Fir 6" dia., bears N.84°W., 12 lks. dist. mkd. ¼ S36 BT.

Douglas Co. Surveyors Office - John M. Powell, and crew - Oct. 27, 1969 - C.S. File 54/94-18

Found - No trace of NW. BT or Stone, as they fall in the road.

10" W.Fir now dead, N.6°E., 37.6 ft., scribe visible
Set Brass cap for WIT. COR. mkd. County Surveyors Office
T 26 S R 1 W
W.C. 55' East to
S 36
T27S

New BT - 28" D.Fir N.74°W., 94.5 ft. mkd. W.C. ¼ S36 CS BT.
Bearing Object: RR spike in rock cut bank N.36°E., 47.1 ft., 4 ft. above road.

Douglas Co. Surveyors Office - John M. Powell, and crew - May 21, 1973 - C.S. File 56/25-29

Found - 28" D.Fir N.74°W., 94.5 ft., face pitched over.
R.R. spike in rock cut bank, N.36°E., 47.1 ft., 4 ft. above road.

Orig. 10" W.Fir N.6°E., 37.6 ft.
Wit. Cor. brass cap out of ground mkd. in 1969.
RESET brass cap at correct location for Wit. Corner.