TOWNSHIP 26 RANGE 01 POINT IDENTIFIER # 640200

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 25 & 36

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by Fred Mensch, Deputy Surveyor - contract #797 dated April 19, 1910 - (DCSO records Vol. 10 Page(s) 4104)

Set a conglomerate stone 15x12x8", 10" in the ground for ¼ sec. cor. mkd. ¼ on N face, from which
A hemlock, 7" dia., bears N.9°E., 17 lks., mkd: ¼ S25 BT.
A fir, 48" dia., bears South, 9 lks., mkd: ¼ S36 BT.

Douglas Co. Surveyors Office - Karen Cheney - James Cook - A. Victor Cangie - 5/25/1976 - C.S. File 59/15-7

Found - A conglomerate stone 15x12x8" with "¼" marked on North face. From Which -
An original 7" Hemlock bears N.19°E., 11.2 ft. Visible scribing "4 S25 BT". Alive and well.
A 48" downed fir, hole hits good for called bearing and dist. No visible blaze.

Set - At corner point established from orig NE BT a 1x30" IP with brass cap marked: Douglas County Surveyor
T26S R1W
¼ S 25
S 36
1976

NOTE - On North side of brass cap replaced original stone.

New BT - A 16" Hemlock bears S.21°E., 24.3 ft. marked "¼ S36 CS BT" in double blaze.
Compass dec. 20° East.