

TOWNSHIP 26 RANGE 01 POINT IDENTIFIER # 640400

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 13 & 24

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO survey by Fred Mensch, Deputy Surveyor - contract #797 dated April 19, 1910 - (DCSO records Vol. 10 Page(s) 4108)

A fir, 48" dia., for ¼ sec. cor. I mark ¼ on S13 on N & 24 on S side, from which
 A hemlock, 5" dia., bears N.34°W., 7 lks., mkd: ¼ S13 BT.
 A hemlock, 6" dia., bears S.74°E., 27 lks., mkd: ¼ S24 BT.

Dennis Gaylord, USFS - Douglas Co. Surveyors Office -
Witness: James Davis - Sept. 14, 1978 - C.S. File 60/17-6

Found - Orig. corner tree is now a 45" snag (D.Fir)
 Previously opened blaze on North side but face is decayed. Scribing and reverse is visible on South side of tree, "24".
 No other accessories remaining.
Set - I set a 1½" IP with a 2½" brass cap stamped: County Surveyors Office T26S R1W ¼ S13 S24 WC West 6.0 FT 1978" as a witness corner. Brass cap bears East, 6.0 ft. from center of corner tree snag.
New BTs- A 11" D.Fir bears N.45°E., 41.5 ft. scribed "¼ S13 CS BT" on a double blaze.
 A 10" D.Fir bears S.60°E., 27.9 ft. scribed "¼ S24 CS BT" on a double blaze.
Trees are from the corner tree snag.
Placed County BT signs on all BTs.