

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 1 & 12

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by Fred Mensch, Deputy Surveyor - contract #797 dated April 19, 1910 - (DCSO records Vol. 10 Page(s) 4111-2)

Set a conglomerate stone 12x10x8", 8" in the ground for ¼ sec. cor. mkd. ¼ on N face, from which

A fir, 18" dia., bears N.12°W., 21 lks., mkd: ¼ S1 BT.

A cedar, 36" dia., bears S.37°W., 48 lks., mkd: ¼ S12 BT.

Douglas Co. Surveyors Office - Randall Smith, Deputy - Stephen Flause - Terrie Franssen - April 5, 1991 - C.S. 64/13-17

Found - Orig. stone, top measures 10"x5", protruding 5" above ground, chiseled "¼" on north side. 36" now 38" dia. tipped out of ground burnt cedar, no scribing or blazes found, root hole bears S.37°W., 31.7 ft. (agrees with record) Orig BT. Original NW BT not found.

Set - Orig. stone is referenced, stone measures 10x5x9" with smaller fractured pieces near. (Rec. 12x10x8").

A 2 3/8" dia. DCSO brass cap on a 1 3/8 O.D. x 32" long iron pipe is set at referenced position & protrudes 12" above ground. A 2 ft. dia. mound of stones is placed around base of BC/IP with marked orig stone along north edge of BC/IP "1/4" faces North. BC/IP protrudes 5" above mound of stone. Cap mkd: Douglas County Surveyors T26S ¼ S1 S12 R1W 1991 Office.

New BTs- 5" dia. D.Fir, double blazed and scribed "¼ S12 CS BT" bears S.4°E., 13.3 ft.

28" dia. sugar pine, double blazed and scribed "¼ S12 CS BT" bears S.68°E., 18.5 ft.

5" dia. chinquapin, double blazed and scribed "¼ S1 CS BT" bears N.86½°E., 13.9 ft.

17" dia. D.Fir double blazed and scribed "¼ S1 CS BT" bears N.44½°W., 18.4 ft.