

PRIMARY CORNER DESCRIPTION Sec Cor for 35 & 36 only, T25-1

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by Hezekiah H. Johnson, Deputy Surveyor, under Contract #721, dated May 1, 1900 - (DCSO records Vol. 8 Page(s) 3500)

The point for sec. cor. falls on a projecting point of rock in place, 18x12x6 ins., above ground. At the exact cor point, I cut a cross (+) for cor. of secs. 1, 2, 35 and 36 and mark 5 grooves on W., 1 groove on E. of cross, from which
A Point of rock 3 ft. high, bears N.45°E., 19 lks. dist. mkd. + - B.O.
A Fir 10" dia., bears S.26°E., 87 lks. dist. mkd. T26S R1W S1 BT.
A Fir 18" dia., bears S.85°W., 74 lks. dist. mkd. T26S R1W S2 BT.
A Maple 4" dia., bears N.70°W., 63 lks. dist. mkd. T25S R1W S35 BT.

GLO resurvey by Fred Mensch, U.S. Cadastral Engineer - under Contract #797, dated April 19, 1910 - (DCSO records Vol. 9 Page(s) 3571) and Duplicate Pgs. 4078-79)

This cor. is partially obliterated, no trace being found of the cor. or the NW. bearing tree. The other BTs and the bearing rock are found. I Re-Establish the cor. in its original position as the cor. of secs. 35 and 36, T25S R1W only, as follows:
Point for the corner falls on a basalt rock in place, 18x12x6 ins., above ground on which I cut a cross (+) at exact corner point, with 1 notch E. and 5 notches W. of cross, from which
A Point of rock, 3 ft. high, bears N.45°E., 19 lks. dist. mkd. B O 36.
A Maple 6" dia., bears N.76½°W., 73 lks. dist. mkd. T25S R1W S35 BT.
I obliterate marks on former bearing trees referring to T26S.

Fd. OK and used in GLO resurvey by Otto L. Draper, U.S. Transitman, March 12, 1921 - (DCSO records Vol. 22 Page(s) 9239)

Douglas Co. Surveyors Office - Milo E. Godfrey, Deputy - Vernon Tracy; Clete Putnam, crew - June 6, 1962 - C.S. File 52/30-4

Found - "X" on rock in place, nearly buried under loose material.
"B.O." chiseled on rock outcrop, N.45°E., 12.5 ft.
Stump hole and Maple sprouts, N.76½°W., 48.2 ft.
(Cont. Next Page)

TOWNSHIP 26 RANGE 01 POINT IDENTIFIER # 657700

PRIMARY CORNER DESCRIPTION Sec Cor for 35 & 36 only, T25-1

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

Impossible to set brass cap solidly at corner position.
New BTs- 6" W.Oak, N.39°E., 23.4 ft. mkd. S36 CS BT.
18" D.Fir S.48°W., 12.0 ft. mkd. T25S S35 S36 CS BT
No good trees available NW. of corner.

Fd. OK. DCSO, V. Tracy, Oct. 17, 1966

Romanso E. Ware - For: U.S. Forest Service - Sept. 1978 -
M 73-69

Found - 1.2 ft. x 1 ft. x 1 ft. slate rock with "X".
25" D.Fir bears S.48°W., 12 ft., good scar.
6" W.Oak bears N.39°E., 23.4 ft., good scar.
Set 3" brass cap in rock. Steel fence post 4 ft. North. Cap
stamped "T25S R1W S.C. S 35 S36 L.S. 1005 1978".
New BT - 7" B.Oak bears N.50°W., 26.9 ft. with washer scribed
"T25S R1W S35 BT".