

PRIMARY CORNER DESCRIPTION E. 1/4 Cor. for Sec. 36 only

Alias	Description
Alias	Description
Alias	Description
Alias	Description

GLO survey by Fred Mensch, Deputy Surveyor, under Contract #797, dated April 19, 1910 - (DCSO records Vol. 10 Page(s) 4070)

Set a conglomerate stone 18x12x12 ins., 12" in the ground for 1/4 sec. cor. marked 1/4 on W. face, from which
A Fir 30" dia., bears S.39°E., 8 lks. dist. mkd. 1/4 S31 BT.
A Fir 10" dia., bears S.64°W., 19 lks. dist. mkd. 1/4 S36 BT.

GLO resurvey by Otto L. Draper, U.S. Transitman, under Special Instructions, dated Dec. 24, 1920 - (DCSO records Vol. 22 Page(s) 9520)

Intersect the old 1/4 sec. cor., established for secs. 31 and 36, which is a conglomerate stone 16x12x9 ins. above ground, marked 1/4 on the W. face. I change this cor. to refer to sec. 36 only, obliterating the scribe marks on the SE. BT.
Alongside of old cor. stone, SET an iron post 3 ft. long, 1" dia., 27" in the ground, for the 1/4 sec. cor. of sec. 36 only, with brass cap mkd. 1/4 S 36
1928

from which
A Fir 33" dia., bears S.39°E., 8 lks. dist. mkd. 1/4 S31 BT.
(Old bearing tree)
A Fir 14" dia., bears S.64°W., 19 lks. dist. mkd. 1/4 S36 BT. (Old bearing tree)
A Fir 10" dia., bears N.20°W., 19 lks. dist. mkd. 1/4 S36 BT