

PRIMARY CORNER DESCRIPTION Sec. Cor. for 24 & 25 only, (East)

Alias	Description
Alias	Description
Alias	Description
Alias	Description

GLO survey by Fred Mensch, Deputy Surveyor, under Contract #797, dated April 19, 1910 - (DCSO records Vol. 10 Page(s) 4071-72)

Set a basalt stone 14x8x5 ins., 9½" in the ground for cor. of secs. 19, 24, 25 and 30, marked with 4 notches on N. and 2 notches on S. edge, from which
A Hemlock 16" dia., bears N.44°E., 41 lks. dist. mkd. T26S R1E S19 BT.
A Hemlock 10" dia., bears S.45°E., 8 lks. dist. mkd. T26S R1E S30 BT.
A Hemlock 10" dia., bears S.61°W., 20 lks. dist. mkd. T26S R1W S25 BT.
A Yew 5" dia., bears N.71°W., 20 lks. dist. mkd. T25S R1W S24 BT.

GLO resurvey by Otto L. Draper, U.S. Transitman, under Special Instructions, dated Dec. 24, 1920 - (DCSO records Vol. 22 Page(s) 9523-24)

Intersect the cor., established for secs. 19, 24, 25 and 30 which is a basalt stone, 10x7x5 ins. above ground, marked with 4 notches on the N. and 2 notches on the S. edge. I change this cor. to refer to secs. 24 and 25 only, obliterating the scribe marks on the NE. and SE. bearing trees. Alongside of old stone cor., SET an iron post 3 ft. long, 2" in dia., 27" in the ground for cor. of secs. 24 and 25 only, with brass cap marked:
T26S T26S
S 24 S30
S 25
R 1W R 1 E
1928

from which the original bearing trees,
A Hemlock 20" dia., bears N.44°E., 41 lks. dist. mkd. T26S R1E S19 BT.
A Hemlock 10" dia., bears S.45°E., 8 lks. dist. mkd. T26S R1E S30 BT.
A Hemlock 12" dia., bears S.61°W., 20 lks. dist. mkd. T26S R1W S25 BT.
A Yew 6" dia., bears N.71°W., 20 lks. dist. mkd. T26S R1W S24 BT.