

PRIMARY CORNER DESCRIPTION Sec. Cor. for 13 & 24 only (East)

Alias	Description
Alias	Description
Alias	Description
Alias	Description

GLO survey by Fred Mensch, Deputy Surveyor, under Contract #797, dated April 19, 1910 - (DCSO records Vol. 10 Page(s) 4073)

- 
- Set a basalt stone 15x10x8 ins., 10" in the ground for cor. of secs. 13, 18, 19 and 24, marked with 3 notches on N. and S. edges, from which
- A Fir 18" dia., bears N.30½°E., 87 lks. dist. mkd. T26S R1E S18 BT.
  - A Madrone 5" dia., bears S.83¼°E., 83 lks. dist. mkd. T26S R1E S19 BT.
  - A Fir 14" dia., bears S.87°W., 100 lks. dist. mkd. T26S R1W S24 BT.
  - A Fir 30" dia., bears N.47°W., 205 lks. dist. mkd. T26S R1W S13 BT.

GLO resurvey by Otto L. Draper, U.S. Transitman, under Special Instructions, dated Dec. 24, 1920 - (DCSO records Vol. 22 Page(s) 9525-26)

- 
- Intersect the old cor., established for sec. 13, 18, 19 and 24, which is a basalt stone, 6x5x4 ins. above ground, marked with 3 notches on the N. and 3 notches on the S. edge. I change this cor. to refer to secs. 13 and 24 only, obliterating the scribe marks on the NE. and SE. bearing trees, from which
- A Fir 24" dia., bears N.30½°E., 87 lks. dist. mkd. T26S R1E S18 BT. (Old BT)
  - A Madrone 5" dia., bears S.83¼°E., 83 lks. dist. mkd. T26S R1E S19 BT. (Old BT)
  - A Fir 18" dia., bears S.87°W., 83 lks. dist. (not 100 lks.) marked T26S R1W S24 BT. (Old BT)
  - A Fir 32" dia., bears N.51°W., 211 lks. dist. (not N.47°W., 205 lks.) marked T26S R1W S13 BT. (Old BT)