

PRIMARY CORNER DESCRIPTION E. 1/4 Cor. for Sec. 13 only

Alias	Description
Alias	Description
Alias	Description
Alias	Description

GLO survey by Fred Mensch, Deputy Surveyor, under Contract #797, dated April 19, 1910 - (DCSO records Vol. 10 Page(s) 4074)

(40.00 chs.)
Point for ¼ sec. cor. on face of bluff.
(42.55 chs. - North)
A Basalt rock in place, 3x2x2 ft. above ground, for witness cor. to the ¼ sec. cor., I mark with a cross (X) at exact cor. point, WC ¼ W. of cross, from which
A Fir 12" dia., bears S.43½°E., 131 lks. dist. mkd. WC ¼ S18 BT.
A W.Oak 8" dia., bears N.26½°W., 89 lks. dist. mkd. WC ¼ S13 BT.

GLO resurvey by Otto L. Draper, U.S. Transitman, under Special Instructions, dated Dec. 24, 1920 - (DCSO records Vol. 22 Page(s) 9526-27)

Intersect the old witness ¼ sec. cor., established for secs. 13 and 18, which is a basalt stone in place, 3x2x2 ft. above ground marked with a cross (X) at exact cor. point and W C ¼ to the W. of cross. (Note: This cor. was originally set 2.55 chs. N. of the true point for cor., and the ground is too rough to change this cor. to its true position.)
This cor. will hereafter refer to sec. 13 only.
No trace of either of the old BTs was found, from which the new bearing trees:
An Oak 9" dia., bears N.60°W., 98 lks. dist. mkd. WC ¼ S13 BT.
A Fir 30" dia., bears N.30°W., 221 lks. dist. mkd. WC ¼ S13 BT.