

PRIMARY CORNER DESCRIPTION E. 1/4 Cor. for Sec. 12 only

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by Fred Mensch, Deputy Surveyor, under Contract #797, dated April 19, 1910 - (DCSO records Vol. 10 Page(s) 4075)

Point for ¼ sec. cor. falls on a basalt rock in place, 4x8x6 ins., above ground on which I cut a cross (X) at exact cor. point, ¼ W. of cross, from which
A Fir 7" dia., bears S.61°E., 23 lks. dist. mkd. ¼ S7 BT.
A Fir 5" dia., bears S.80½°W., 17 lks. dist. mkd. ¼ S12 BT.

GLO resurvey by Otto L. Draper, U.S. Transitman, under Special Instructions, dated Dec. 24, 1920 - (DCSO records Vol. 22 Page(s) 9529)

Intersect the old ¼ sec. cor., established for secs. 7 and 12, which is a basalt stone, 18x12x6 ins. above ground, marked with a cross (X) at exact cor. point and ¼ W. of cross. I change this cor. to refer to sec. 12 only, obliterating the marks on the old SE. bearing tree, from which
A Fir stump 8" dia., bears S.61°E., 23 lks. mkd. ¼ S7 BT (Old BT)
A fallen Fir 7" dia., bears S.80½°W., 17 lks. mkd. ¼ S12 BT. (Old BT)
A Fir 6" dia., bears S.45°W., 52 lks. dist. mkd. ¼ S12 BT.
A Fir 6" dia., bears N.25°W., 43 lks. dist. mkd. ¼ S12 BT.

Douglas Co. Surveyors Office - Randall Smith and Stephen Flause, Terrie Franssen crew - April 4, 1991 - C.S. File 64/13-19

Found - 18"x12" stone with a chiseled "+" on top, protruding 6" above ground. (Original) Stone is firmly set. No original BTs found.
6" now 33" dia. D.Fir with a fully healed double blaze, S.45°W., 35.3 ft. (Rec. S.45°W., 34.3 ft.)
6" now 23" dia. D.Fir with a fully healed single blaze, bears N.25°W., 28.4 ft. (agrees w/rec.)
Original stone is in good shape, goes into ground and gets larger, does not appear to be easily moved. We did not set a brass cap for corner.
New BTs- 8" dia. D.Fir, double blazed and scribed "¼ S12 CS BT", bears N.83½°W., 9.8 ft.
7" dia. D.Fir, double blazed and scribed "¼ S12 CS BT", bears S.35°W., 8.2 ft.
Corner lies on a westerly slope.