

TOWNSHIP 26 RANGE 01 POINT IDENTIFIER # 700547

PRIMARY CORNER DESCRIPTION W. 1/4 Cor. for Sec. 7 only, T26-1E

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO resurvey by Otto L. Draper, U.S. Transitman, under Special Instructions, dated Dec. 24, 1920 - (DCSO records Vol. 22 Page(s) 9529)

Set an Iron post 3 ft. long, 1" dia., 27" in the ground for the ¼ sec. cor. of sec. 7 only, with brass cap mkd. ¼ S7
1928

from which

A Fir 20" dia., bears N.60°E., 29 lks. dist. mkd. ¼ S7 BT
Raise a mound of stone with a base 3 ft., 2 ft. high E. of cor., as no other bearing tree was available.

Douglas Co. Surveyors Office - Randall Smith and Stephen Flause, Terrie Franssen, crew - April 4, 1991 - C.S. File 64/13-18

Found - 1928 2½" dia. GLO brass cap on a 1" O.D. Iron pipe protruding 11" above ground. A 2 ft. dia. mound of stone is found along East edge of BC/IP (Rec., raised mound of stone 3 ft., 2 ft. high E. of cor.) (orig. Cor.)

20" now 39" dia. D.Fir with a fully healed single blaze, bears N.56°E., 19.1 ft. (Rec. N.60°E., 19.1 ft. (Orig. BT)

New BTs- 14" dia. D.Fir double blazed and scribed "¼ S7 CS BT", bears S.28°E., 4.6 ft.

15" dia. D.Fir double blazed and scribed "¼ S7 CS BT", bears S.2°E., 34.8 ft.

8" dia. D.Fir double blazed and scribed "¼ S7 CS BT", bears N.71°E., 32.7 ft.

Corner lies on a westerly slope.