

TOWNSHIP 26 RANGE 01 POINT IDENTIFIER # 700647

PRIMARY CORNER DESCRIPTION W. 1/4 Cor. for Sec. 6 only, T26-1E

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO resurvey by Otto L. Draper, U.S. Transitman, under Special Instructions, dated Dec. 24, 1920 - (DCSO records Vol. 22 Page(s) 9531)

Set an Iron post 3 ft. long, 1" dia., 27" in the ground for the ¼ sec. cor. of sec. 6 only, with brass cap mkd. ¼ S 6
1928
from which
A Fir 30" dia., bears N.25°E., 43 lks. dist. mkd. ¼ S6 BT.
A Fir 18" dia., bears S.18°E., 21 lks. dist. mkd. ¼ S6 BT.

Survey by Maurice E. Farr, LS #1181 - For: U.S. Forest Service - Nov. 1986 - C.S. File 62/33-3

Found - Orig. GLO 1928 brass cap, properly mkd. on 1" dia. Iron pipe is firmly set, projecting 10" above the ground.
A root hole bears N.25°E., 28.4 ft. with decayed log along side, size indeterminate, with no marks visible.
A decayed stump, size indeterminate, bears S.18°E., 13.9 ft. with no marks visible.
New BTs- A 10" W.Fir bears N.73°E., 25.5 ft. scribed "¼ S6 BT" on a single blaze with a 3/4" brass washer, stamped "LS 1181" nailed flush to base of blaze.
A 5" W.Fir bears S.18°E., 16.6 ft. scribed "XBT" on a single blaze with a 3/4" brass washer, stamped "LS 1181" nailed flush to base of blaze.
I SET a 6 ft. long alum. post, driven 2 ft. in the ground, as a guard post, bears North, 2.0 ft. with Forest Service sign #54-4 attached. To reach corner, drive 1.4 miles up F.S. Road #4712-010, thence approx. 400 ft. West.

James M. Stanley, ODOT - Sept/Nov. 2007 - St. Hwy 138-011V

Fd. 2¼" Brass cap stamped "US General Land Office Survey ¼ S6 1928" (10-30-07)
N. 616636.402
E. 4321961.158