

TOWNSHIP 26 RANGE 01 POINT IDENTIFIER # 700669

PRIMARY CORNER DESCRIPTION NW Cor. S6, T26-1E; SW Cor S31, T25½-1E

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

GL0 resurvey by Otto L. Draper, U.S. Transitman, under Special Instructions, dated Dec. 24, 1920 - (DCSO records Vol. 22 Page(s) 9549)

-----  
Intersect the Willamette Meridian, 47.75 chs. N.0°04'E., of the ¼ sec. cor. of sec. 1 only, (T26-1W). At point of intersection, Set an Iron post 3 ft. long, 3" dia., 16" in the ground to bedrock, supported in a mound of stone, with a 4 ft. base, 1 ft. high, for the closing Tp. cor. of Tps. 25½ and 26 S., R1E. with brass cap marked:

T26S	T25½S
R1W	R1E
S 1	<u>S 31</u> CC
	<u>S 6</u>
	T26S
	1928

from which

A Fir 10" dia., bears N.17°E., 62 lks. dist. mkd. T25½ R1E  
S31 CC BT.

An Oak 4" dia., bears S.89°E., 41 lks. dist. mkd. T26S R1E  
S6 CC BT.

Douglas Co. Surveyors Office - Crew: Stephen Flause & Jeff Lorsung- 5/9/2024 - C.S. File 67/57-57

-----  
Monument not found; using measured ties to the west ¼ corner of section 6, the section corner 73.23 chains east and GPS positioning, no corner evidence is found in the determined search area.