

TOWNSHIP 26 RANGE 02E POINT IDENTIFIER # 100200

PRIMARY CORNER DESCRIPTION Cor. Secs. 30, 31; 25, & 36; T26-1E

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

GLO survey by Otto L. Draper, US Transitman, under Special Instructions dated Dec. 24, 1920 - (DCSO records Vol. 22 Page(s) 9533-4)

-----  
Set an iron post, 3 ft. long, 2" dia., 27" in the ground, for cor. of secs. 25, 30, 31, & 36, with brass cap mkd

T26S  
R1E | R2E  
S 25 | S 30  
S 36 | S 31  
1928

from which

- A fir, 16" dia., bears N.3°E., 46 lks., mkd: T26S R2E S30  
BT.
- A 14, 32" dia., bears S.32°E., 33 lks., mkd: T26S R2E S31  
BT.
- A fir, 20" dia., bears S.56°W., 48 lks., mkd: T26S R1E S36  
BT.
- A fir, 36" dia., bears N.50°W., 24 lks., mkd: T26S R1E S25  
BT.