

TOWNSHIP 26 RANGE 02E POINT IDENTIFIER # 100400

PRIMARY CORNER DESCRIPTION Cor. Secs. 18, 19, 13, & 24 T26-1E

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

GLO survey by Otto L. Draper, US Transitman, under Special Instructions dated Dec. 24, 1920 - (DCSO records Vol. 22 Page(s) 9536)

-----

Set an iron post, 3 ft. long, 2" dia., 27" in the ground, for cor. of secs. 13, 18, 19, & 24, with brass cap mkd

T26S	
R1E	R2E
S 13	S 18
S 24	S 19
1928	

from which

- A fir, 12" dia., bears N.7°E., 52 lks., mkd: T26S R2E S18 BT.
- A fir, 12" dia., bears S.39°E., 136 lks., mkd: T26S R2E S19 BT.
- A fir, 30" dia., bears S.37°W., 140 lks., mkd: T26S R1E S24 BT.
- A fir, 12" dia., bears N.11°W., 60 lks., mkd: T26S R1E S13 BT.