

TOWNSHIP 26 RANGE 02E POINT IDENTIFIER # 100500

PRIMARY CORNER DESCRIPTION Cor. Secs. 7, 12, 13, & 18 T26-1E

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

GLO survey by Otto L. Draper, US Transitman, under Special Instructions dated Dec. 24, 1920 - (DCSO records Vol. 22 Page(s) 9537-8)

-----  
Set an iron post, 3 ft. long, 2" dia., 27" in the ground, for cor. of secs. 7, 12, 13, & 18, with brass cap mkd

T26S  
R1E | R2E  
S 12 | S 7  
S 13 | S 18  
1928

from which

- A fir, 4" dia., bears N.37°E., 19 lks., mkd: T26S R2E S7  
BT.
- A fir, 8" dia., bears S.35°E., 19 lks., mkd: T26S R2E S18  
BT.
- A fir, 20" dia., bears S.49°W., 57 lks., mkd: T26S R1E S13  
BT.
- A fir, 18" dia., bears N.80°W., 52 lks., mkd: T26S R1E S12  
BT.