

TOWNSHIP 26 RANGE 02E POINT IDENTIFIER # 200200

PRIMARY CORNER DESCRIPTION Cor. Secs. 29, 30, 31, & 32

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

GLO Survey by Otto S. Draper, U.S. Transitman, under Special Instructions dated Dec. 24, 1920, surveyed Sept. 1929/Aug. 1930 - (DCSO records Vol. 23 Page(s) 9702-3

-----  
Set an iron post, 3 ft. long, 2" dia., 27" in the ground, for cor. of secs. 29, 30, 31, & 32, with brass cap mkd

T26S R2E  
S30|S29  
S31|S32  
1929

from which

- A fir, 14" dia., bears N.41°E., 69 lks., mkd: T26S R2E S29 BT.
- A fir, 42" dia., bears S.20°E., 21 lks., mkd: T26S R2E S32 BT.
- A fir, 24" dia., bears S.36°W., 143 lks., mkd: T26S R2E S31 BT.
- A fir, 40" dia., bears N.33°W., 81 lks., mkd: T26S R2E S30 BT.