

PRIMARY CORNER DESCRIPTION Cor Secs 17, 18, 19, & 20

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO Survey by Otto S. Draper, U.S. Transitman, under Special Instructions dated Dec. 24, 1920, surveyed Sept. 1929/Aug. 1930 - (DCSO records Vol. 23 Page(s) 9710

-----  
Set an iron post, 3 ft. long, 2" dia., 28" in the ground, for cor. of secs. 17, 18, 19, & 20, with brass cap mkd

T26S R2E  
S18|S17  
S19|S20  
1929

from which

- A pine, 20" dia., bears N.17°E., 79 lks., mkd: T26S R2E S17 BT.
- A fir, 40" dia., bears S.1½°E., 119 lks., mkd: T26S R2E S20 BT.
- A fir, 42" dia., bears S.9°W., 151 lks., mkd: T26S R2E S19 BT.
- A fir, 50" dia., bears N.85°W., 236 lks., mkd: T26S R2E S18 BT.

Robert Dean, LS #1808 - For: U.S. Forest Service - Nov. 11,1984 - N 97-60 & C.S. file 58/204

-----  
Found - 1½" galv. IP & 2½" brass cap in a 36" cairn. (1929 GLO)

- A 54" D.Fir, good scar, bears N.84°08'W., 154.7 ft. (Rec. N.85°W., 155.76 ft.)
- A 25" ponderosa pine, scribing visible in low face, bears N.17°22'E., 52.6 ft. (Rec. N.17°E., 52.14 ft)
- A 45" D.Fir, good scar, bears S.1°00'W., 78.0 ft. (Rec. S.1½°E 78.54 ft.)
- A 47" dead D.Fir, rooted scar, bears S.8°42'W., 100.3 ft. (Rec. S.9°W., 99.66 ft.)
- New BT- A 13" D.Fir, scribed "T26S R2E S19 BT" bears S.52°54'W., 41.3 ft.
- A 3/4" brass disc stamped "RLS 1808" is nailed low to the face.