

TOWNSHIP 26 RANGE 02E POINT IDENTIFIER # 200640

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 5 & 6

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO Survey by Otto S. Draper, U.S. Transitman, under Special Instructions dated Dec. 24, 1920, surveyed Sept. 1929/Aug. 1930 - (DCSO records Vol. 23 Page(s) 9721

Set an iron post, 3 ft. long, 1" dia., 28" in the ground, for 1/4 cor. of secs. 6 & 5, with brass cap mkd

1/4
S6|S5
1930

from which

- A fir, 12" dia., bears N.41°E., 78 lks., mkd: 1/4 S5 BT.
- A fir, 12" dia., bears N.33°W., 46 lks., mkd: 1/4 S6 BT.

Richard C. Grant - 8/1966 - C.S. File 55/71

Found - 1930 GLO Brass Cap, pipe buried 6" below surface on edge of gravel.

Note - Road destroyed old bearing trees.

- New BTs- 50" D.Fir S.85°W. 40.3 ft., mkd: 1/4 Cor. S6 T26S R2E 2807".
- 48" D.Fir N.76°E. 51.7 ft., mkd: "1/4 Cor. S5 T26S R2E 2807."