

TOWNSHIP 26 RANGE 02E POINT IDENTIFIER # 300400

PRIMARY CORNER DESCRIPTION Cor. Secs. 16, 17, 20, & 21

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

GLO Survey by Otto S. Draper, U.S. Transitman, under Special Instructions dated Dec. 24, 1920, surveyed Sept. 1929/Aug. 1930 - (DCSO records Vol. 23 Page(s) 9693-4

-----  
Set an iron post, 3 ft. long, 2" dia., 28" in the ground, for cor. of secs. 16, 17, 20, & 21, with brass cap mkd

T26S R2E  
S17|S16  
S20|S21  
1929

from which

- A fir, 30" dia., bears N.29°E., 25 lks., mkd: T26S R2E S16  
BT.
- A fir, 22" dia., bears S.69°E., 51 lks., mkd: T26S R2E S21  
BT.
- A fir, 30" dia., bears S.88°W., 56 lks., mkd: T26S R2E S20  
BT.
- A fir, 32" dia., bears N.35°W., 18 lks., mkd: T26S R2E S17  
BT.