

TOWNSHIP 26 RANGE 02E POINT IDENTIFIER # 400400

PRIMARY CORNER DESCRIPTION Cor. Secs. 15, 16, 21, & 22

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO Survey by Otto S. Draper, U.S. Transitman, under Special Instructions dated Dec. 24, 1920, surveyed Sept. 1929/Aug. 1930 - (DCSO records Vol. 23 Page(s) 9679

Set an iron post, 3 ft. long, 2" dia., 29" in the ground, for cor. of secs. 15, 16, 21, & 22, with brass cap mkd

T26S R2E
S16|S15
S21|S22
1929

from which

- A pine, 20" dia., bears N.86°E., 102 lks., mkd: T26S R2E S15 BT.
- A pine, 12" dia., bears S.69°E., 99 lks., mkd: T26S R2E S22 BT.
- A pine, 20" dia., bears S.8°W., 91 lks., mkd: T26S R2E S21 BT.
- A pine, 26" dia., bears N.80°W., 478 lks., mkd: T26S R2E S16 BT.

Douglas Co. Surveyors Office - Vernon "Ray" Tracy - JGH & VDP - Oct. 1969 - C.S. File 54/43-18

Reported as not found
No OBTs or brass cap fd., probably due to cultivation & clearing.