

TOWNSHIP 26 RANGE 02E POINT IDENTIFIER # 400440

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 15 & 16

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO Survey by Otto S. Draper, U.S. Transitman, under Special Instructions dated Dec. 24, 1920, surveyed Sept. 1929/Aug. 1930 - (DCSO records Vol. 23 Page(s) 9681

Set an iron post, 3 ft. long, 1" dia., 27" in the ground, for 1/4 cor. of secs. 15 & 16, with brass cap mkd

1/4
S16|S15
1929

from which

- A fir, 34" dia., bears N.80°E., 100 lks., mkd: 1/4 S15 BT.
- A fir, 18" dia., bears N.45°W., 46 lks., mkd: 1/4 S16 BT.

Robert Dean, LS 1808 - For: USFS - Dec. 20, 1984 - M98-6 & C.S. File 58/204

Condition report

Found - 3/4" galv. I.P. with 2 1/2" brass cap marked "US General Land Office Survey Penalty \$350 for Removal 1/4 S16 S15 1929".

From which

- A 25" D.Fir, healed scar, bears N.44°30'W., 32.3 ft. (Record N.45°W., 30.36 ft. per GLO)
- A 35" D.Fir, healed scar, bears N.81°15'E., 67.4 ft. (Record N.80°E., 66.00 ft. per GLO)

Cairn built to 36" around the pipe.