

TOWNSHIP 26 RANGE 02E POINT IDENTIFIER # 500440

PRIMARY CORNER DESCRIPTION 1/4 Cor Secs 14 & 15, Witness corner

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO Survey by Otto S. Draper, U.S. Transitman, under Special Instructions dated Dec. 24, 1920, surveyed Sept. 1929/Aug. 1930 - (DCSO records Vol. 23 Page(s) 9667

Set an iron post, 3 ft. long, 1" dia., 27" in the ground, for witness cor. to ¼ cor. of secs. 24 & 25, with brass cap mkd

¼
S15|S14
W|C
1929

from which

A fir, 6" dia., bears S.65°E., 29 lks., mkd: WC ¼ S14 BT.

A pine, 18" dia., bears N.32°W., 25 lks., mkd: WC ¼ S15 BT

Kristian DeGroot, PLS 1941 - For: USFS - Crew: Les Fanning, Matt Dixon, & Aaron Fanning - March 1998 - C.S. File 65/20-11

Found - 1" OD iron pipe, firmly set, projecting 10" above the ground with a 2½" brass cap properly stamped. GLO 1929

A root hole bears N.32°W., 16.5 ft. GLO 1929

13" Fir bears S.65°E., 19.1 ft with a healed blaze. GLO 1929

New - I rebuild a mound of stone, 42" dia. base to top of monument.

13" D.Fir bears N.9°30'W., 22.5 ft. scribed "WC ¼ S15 BT" with a brass washer stamped "PLS 1941" nailed in lower blaze.

Paint a 6" red band and BT face red and nail USFS "BEARING TREE" and "LAND SURVEY MONUMENT" signs to all BTs.