

TOWNSHIP 26 RANGE 02E POINT IDENTIFIER # 500700

PRIMARY CORNER DESCRIPTION Cor. Secs. 2, 3, 34 & 35 T25½-2E

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO Survey by Otto S. Draper, U.S. Transitman, under Special Instructions dated Dec. 24, 1920, surveyed Sept. 1929/Aug. 1930 - (DCSO records Vol. 23 Page(s) 9637

A fir, 16" dia., for cor. of secs. 2, 3, 34, & 35 I mark;
T25½S S35 on NE
R2E S2 on SE
T26S S3 on SW
and S34 on NW, sides

from which

- A fir, 14" dia., bears N.64°E., 15 lks., mkd: T25½S R2E S35 BT.
- A cross (X) on face of boulder, 8x8x5 above ground, bears S.16°E., 8 lks., boulder marked X S 2 B O
- A fir, 56" dia., bears S.17°W., 78 lks., mkd: T26S R2E S3 BT.
- A pine, 36" dia., bears N.14°W., 84 lks., mkd: T25½S R2E S34 BT.

Douglas Co. Surveyors Office - Gregory Quibell, Deputy - Teresa Buley - Oct. 28, 1981 - C.S. File 61/29-19

-
- Found - Original corner tree, 16" now 21" fir. Found good scars on NE, SE, SW and NW sides.
Orig. 14" now 18" fir with good scar bears N.64°E., 9.9 ft.
Orig. 8'x8'x5' boulder with "X BO" visible on NW face bears S.16°E., 5.3 ft.
Orig. 56" now 57" fir with good scar bears S.17°W., 51.5 ft.
Orig. 36" now 45" Pine with good scar bears N.14°W., 55.4 ft.
- Set - Put metal tag on south side of corner tree marked: "T25 ½S 35 34 3 2 T26S R2E".
Set concrete nail in 8'x8'x5' boulder just above "X BO" bears S.16°E., 5.3 ft.
- Note - Section corner is at bottom corner of steep clear cut.