

TOWNSHIP 26 RANGE 02E POINT IDENTIFIER # 540300

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 23 & 26

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO Survey by Otto S. Draper, U.S. Transitman, under Special Instructions dated Dec. 24, 1920, surveyed Sept. 1929/Aug. 1930 - (DCSO records Vol. 23 Page(s) 9662-3

Set an iron post, 3 ft. long, 1" dia., 27" in the ground, for 1/4 cor. of secs. 23 & 26, with brass cap mkd

1/4 S23
 S26
 1929

from which

- A pine, 18" dia., bears N.18°E., 61 lks., mkd: 1/4 S23 BT.
- A pine, 14" dia., bears S.35°E., 54 lks., mkd: 1/4 S26 BT.

Robert Dean, LS 1808 - For: USFS - Dec. 1984 - M98-16 & C.S. File 63/5

Found - 3/4" galv. I.P. with 2 1/2" brass cap, 1929 GLO cap properly mkd.

A pine stumphole bears N.16°40'E., 40.8 ft. (Rec. N.18°E., 40.26 ft. per GLO.)

New BTs- 15" D.Fir, scribed "1/4 S26 BT" bears S.18°38'E., 184.6 ft.

15" W.fir scribed "X BT" bears S.71°00'E., 248.5 ft.

A 3/4" brass disc stamped "RLS 1808" is nailed low to the face of each new BT.