

TOWNSHIP 26 RANGE 02E POINT IDENTIFIER # 600400

PRIMARY CORNER DESCRIPTION Cor. Secs. 13, 14, 23, & 24

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO Survey by Otto S. Draper, U.S. Transitman, under Special Instructions dated Dec. 24, 1920, surveyed Sept. 1929/Aug. 1930 - (DCSO records Vol. 23 Page(s) 9650

-----  
Set an iron post, 3 ft. long, 2" dia., 27" in the ground, for cor. of secs. 13, 14, 23, & 24, with brass cap mkd

T26S R2E  
S14|S13  
S23|S24  
1929

Raise a mound of stone, 5 ft. base, 3 ft. high, West of cor. No trees within a reasonable distance.

Kristian DeGroot, PLS 1941 - For: USFS - Crew: Les Fanning, Matt Dixon, & Aaron Fanning - March 1998 - C.S. File 65/20-10

-----  
Found - 2" O.D iron pipe, firmly set, projecting 12" above the ground in a deteriorated mound of stone with a 2½" brass cap properly stamped. GLO 1929

New - I rebuild a mound of stone, 72" dia. base to top of monument.

- 10" D.Fir bears N.13°E., 25.0 ft. scribed "T26S R2W S13 BT"
- 11" D.Fir bears S.10°E., 19.9 ft. scribed "T26S R2W S24 BT"
- 9" D.Fir bears S.35°W., 15.4 ft. scribed "T26S R2W S23 BT"
- 20" D.Fir bears N.3°W., 35.0 ft. scribed "T26S R2W S14 BT"

I nail a brass washer stamped "PLS 1941" into the lower blaze of the new BTs and paint a 6" red band and BT face red and nail USFS "BEARING TREE" & "LAND SURVEY MONUMENT" signs to all BTs